

CHOOSE THE RIGHT OIL FOR YOUR OPERATION

OMNIMAX™ Technology - SynBlend

Component Life

Oil Drain Intervals

Fuel Economy

Fuel Type



CHEVRON DELO® 600 ADF
ULTRA LOW ASH

[Get product details](#)
[15W-40](#)
[10W-30](#)



Improve Engine and After Treatment System Life:
Extend DPF Cleaning 2.5X



Extended Drain Potential
1.7X*



Improvement Potential
3%** 4%**
15W-40 CK-4 10W-30 CK-4

Conventional:
Diesel
Lower Carbon:
Renewable Diesel
Natural Gas
Renewable Natural Gas

APPROVED FOR USE IN MIXED DIESEL AND CNG ENGINE FLEETS

ISOSYN Advanced Technology™ - Synthetic

Component Life

Oil Drain Intervals

Fuel Economy

Fuel Type



CHEVRON DELO 400 XSP

[Get product details](#)
[15W-40](#)
[5W-30](#)
[5W-40](#)
[5W-30 FA-4](#)



Maximize Engine Life:
Improve valve train and piston ring wear protection



Extended Drain Potential
2X*



Improvement Potential
1.6%** 2.3%**
5W-30 CK-4 5W-30 FA-4

Conventional:
Diesel
Gasoline
Lower Carbon:
Renewable Diesel

ISOSYN Advanced Technology - SynBlend

Component Life

Oil Drain Intervals

Fuel Economy

Fuel Type



CHEVRON DELO 400 XLE/SB & ZFA

[Get product details](#)
[15W-40](#)
[10W-30](#)
[10W-30 FA-4](#)



Increase Engine Durability:
Increase scuffing resistance and protection against light duty power cylinder failure by reducing LSPI



Extended Drain Potential
1.5X*



Improvement Potential
1.2%**
10W-30 CK-4

Conventional:
Diesel
Gasoline
Lower Carbon:
Renewable Diesel

ISOSYN Advanced Technology

Component Life

Oil Drain Intervals

Fuel Economy

Fuel Type



CHEVRON DELO 400 SNG

[Get product details](#)
[15W-40](#)



Increase Engine and Service Life:
Exceptional engine wear and ratings for sludge and deposit control



Extended Drain Potential
1.25X*



Lower Carbon:
Natural Gas
Renewable Natural Gas

*Extended oil drain interval (ODI) potential is based on the average of US Class 8 engine manufacturers' recommendations. Results will vary depending upon vehicle/equipment type, fuel consumption, maintenance practices, temperature, and variable driving/operating conditions. Consult the engine/vehicle OEM and Chevron before implementing extended ODIs, especially if the engine/vehicle is under warranty.
**Improvement vs. SAE 15W-40 oil in class 8 diesel engine bench testing. Actual savings will vary depending upon vehicle/equipment type, load, temperature, and variable driving/operating conditions.